

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
13 December 2001 (13.12.2001)

PCT

(10) International Publication Number  
**WO 01/94681 A1**

- (51) International Patent Classification<sup>7</sup>: **D06L 1/02**, C11D 3/16, 7/50
- (21) International Application Number: PCT/US01/18194
- (22) International Filing Date: 5 June 2001 (05.06.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/209,444 5 June 2000 (05.06.2000) US  
09/849,839 4 May 2001 (04.05.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).
- (72) Inventors: **SEVERNS, John, Cort**; 7168 Basswood Drive, West Chester, OH 45069 (US). **HARTMAN, Frederick, Anthony**; 10347 Deerfield Road, Cincinnati, OH 45242 (US). **THOEN, Christiaan, Arthur, Jacques, Kamiel**; 8624 Beckett Point Drive, West Chester, OH 45069 (US). **FRANCE, Paul, Amaat, Raymond, Gerald**; 5240 Barkwood Drive, West Chester, OH 45069 (US). **VINSON, Phillip, Kyle**; 5803 Windermere Lane, Fairfield, OH 45014 (US).
- (74) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— with international search report  
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

WO 01/94681 A1

(54) Title: HOME LAUNDRY METHOD

(57) Abstract: The present invention relates to automatic home laundering processes for cleaning or refreshing fabric articles, especially articles of clothing, linen and drapery. The present invention also relates to automatic home laundering of mixed loads of fabric articles comprising machine washable fabric articles and dry clean only fabric articles. The laundering medium is characterised by a siloxane, preferably a cyclic siloxane.

## HOME LAUNDRY METHOD

5

### RELATED APPLICATIONS

This application claims priority under 35 USC §119(e) to U.S. Provisional Application  
10 Serial No. 60/209, 444 which was filed on June 5, 2000.

### FIELD OF THE INVENTION

The present invention relates to automatic home laundering processes for cleaning or  
refreshing fabric articles, especially articles of clothing, linen and drapery. The present invention  
15 also relates to automatic home laundering of mixed loads of fabric articles comprising machine  
washable fabric articles and dry clean only fabric articles.

### BACKGROUND OF THE INVENTION

For centuries, fabric articles have been washed using water-based processes. In the last  
20 century, this home chore was greatly simplified by the development of the automatic washing  
machine. However, while greatly simplifying the home laundry process, even the home laundry  
process using the automatic washing machine still requires a significant amount of presorting  
fabric articles by color and textures. Typically whites are washed separately from colored fabrics,  
and brightly colored fabric articles (e.g., dark reds and blues) from less highly colored articles.  
25 Further sorting and handling is required when the fabric articles to be laundered include "dry  
clean only" articles.

More recently, water conservation efforts and environmental concerns have driven  
laundry machine manufacturers and laundry detergent manufacturers to reduce the amount of  
water required in the home laundry process. However, such efforts have focused on reducing  
30 water consumption by the wash medium rather than changing the wash medium from a primarily  
water based process.

In parallel, concerns have arisen around the use of "Perc" (short for perchloroethylene) as  
the wash medium for the commercial dry cleaning process. These concerns have led to the  
development of a significant number of proposed alternatives the Perc-based processes, but to

date all other alternatives are still not widely used. Examples include hydrocarbons and liquid carbon dioxide. A more recently proposed option as a replacement for Perc in the commercial dry cleaning field involves the use of siloxanes as the cleaning solution for "dry clean only" fabric articles (see, for example, US Patents: 5,942,007, August 24, 1999; 6,042,617 and 6,042,618, 5 both March 28, 2000; 6,056,789, May 2, 2000; 6,059,845, May 9, 2000; and 6,063,135, May 16, 2000).

It has been discovered by the present invention that further simplification of the automatic home laundry process and elimination of the reliance on a solely water based home laundry process are possible by using a siloxane based wash medium for the home laundry process. This 10 process allows not only the home cleaning of a consumer's "dry clean only" fabric articles, but also those "machine wash" articles conventionally washed at home in a water wash medium. Further while the consumer may still opt to wash such articles separately, the present invention process allows the consumer the freedom to significantly simplify the home laundry process by washing mixed loads of "dry clean only" and "machine wash" articles, thereby greatly reducing 15 the presorting effort.

#### SUMMARY OF THE INVENTION

The present invention encompasses an automatic home laundry process comprising the step of cleaning fabric articles in an automatic washing machine in the home with a wash medium 20 comprising siloxane.

The present invention also relates to an automatic home laundry process comprising contacting, in an automatic washing machine, machine washable fabric articles with a wash medium comprising siloxane. More preferred is the siloxane-containing wash medium comprising less than about 50% water, but in some preferred executions it is desired to include 25 some amount of purposively added water preferably in the range of from about 0.1% to about 50% water by weight of the wash medium.

Further preferred processes of the present invention are directed to an automatic home laundry process comprising contacting, in an automatic washing machine, a mixed load of fabric articles comprising machine washable and dry clean only fabric articles with a wash medium 30 comprising siloxane.

These and other aspects, features and advantages will become apparent from the following detailed description and the appended claims. All percentages, ratios and proportions are by weight, and all temperatures are in degrees Celsius (°C), unless otherwise specified. All

measurements are in SI units unless otherwise specified, and all documents cited are in relevant part incorporated herein by reference in their entirety.

#### DETAILED DESCRIPTION OF THE INVENTION

5           The term "fabric article", as used herein, means any article that is customarily cleaned in a conventional laundry process or in a dry cleaning process. The term encompasses articles of clothing, linen and drapery, clothing accessories, and floor coverings. The term also encompasses other items made in whole or in part of fabric, such as tote bags, furniture covers, tarpaulins and the like.

10           The term "machine washable fabric articles", as used herein, means those fabric articles readily identified by the fabric industry and consumers as safe for laundering by a conventional aqueous automatic home laundry process. Consumers are frequently helped in this identification of fabric articles by manufacturer's tags indentifying the fabric article as "machine washable" or some similar description.

15           The term "dry clean only fabric articles", as used herein, means those fabric articles readily identified by the fabric industry and consumers as unsafe for laundering by a conventional aqueous automatic home laundry process, and instead requiring special handling with a conventional non-aqueous solvent such as Perc. Again, consumers are frequently helped in this identification of fabric articles by manufacturer's tags indentifying the fabric article as "dry clean only" or some similar description.

20           The term "automatic home laundry process", as used herein, means the laundry process as practiced by the consumer using an automatic washing machine, preferably located within the consumer's residence (herein referred to as the process being conducted "in the home"), but also including public laundromats whereby the consumer follows essentially the same laundry process as though the automatic washing machine were present in the home.

25           The term "wash medium", as used herein, means the liquid [including but not limited to, fluid(s) and/or solution(s) and/or solvent(s) and/or emulsion(s)] which is used to wet the fabric articles in the wash load during the automatic home laundry process.

30           The phrase "dry weight of a fabric article" as used herein means the weight of a fabric article that has no intentionally added fluid weight.

          The phrase "absorption capacity of a fabric article" as used herein means the maximum quantity of fluid that can be taken in and retained by a fabric article in its pores and interstices. Absorption capacity of a fabric article is measured in accordance with the following Test Protocol for Measuring Absorption Capacity of a Fabric Article.

**Test Protocol for Measuring the Absorption Capacity of a Fabric Article**

Step 1: Rinse and dry a reservoir or other container into which a siloxane will be added. The reservoir is cleaned to free it from all extraneous matter, particularly soaps, detergents and wetting agents.

Step 2: Weigh a "dry" fabric article to be tested to obtain the "dry" fabric article's weight.

Step 3: Pour 2L of a siloxane at ~20C into the reservoir.

Step 4: Place fabric article from Step 2 into the siloxane-containing reservoir.

Step 5: Agitate the fabric article within the reservoir to ensure no air pockets are left inside the fabric article and it is thoroughly wetted with the siloxane.

Step 6: Remove the fabric article from the siloxane-containing reservoir.

Step 7: Unfold the fabric article, if necessary, so that there is no contact between same or opposite fabric article surfaces.

Step 8: Let the fabric article from Step 7 drip until the drop frequency does not exceed 1 drop/sec.

Step 9: Weigh the "wet" fabric article from Step 8 to obtain the "wet" fabric article's weight.

Step 10: Calculate the amount of siloxane absorbed for the fabric article using the equation below.

$$FA = (W-D)/D*100$$

where:

FA = fluid absorbed, % (i.e., the absorption capacity of the fabric article in terms of % by dry weight of the fabric article)

W = wet specimen weight, g

D = initial specimen weight, g

By the term "non-immersive" it is meant that essentially all of the fluid is in intimate contact with the fabric articles. There is at most minimal amounts of "free" wash liquor. It is unlike an "immersive" process where the washing fluid is a bath in which the fabric articles are either submerged, as in a conventional vertical axis washing machine, or plunged into, as in a conventional horizontal washing machine. The term "non-immersive" is defined in greater detail according to the following Test Protocol for Non-Immersive Processes. A process in which a

fabric article is contacted by a fluid is a non-immersive process when the following Test Protocol is satisfied.

Test Protocol for Non-Immersive Processes

- Step 1: Determine absorption capacity of a fabric specimen using Test Protocol for  
5 Measuring Absorption Capacity of a Fabric Article, described above.

Step 2: Subject a fabric article to a fluid contacting process such that a quantity of the fluid contacts the fabric article.

- Step 3: Place a dry fabric specimen from Step 1 in proximity to the fabric article of Step  
2 and move/agitate/tumble the fabric article and fabric specimen such that fluid transfer from the  
10 fabric article to the fabric specimen takes place (the fabric article and fabric specimen must achieve the same saturation level).

Step 4: Weigh the fabric specimen from Step 3.

Step 5: Calculate the fluid absorbed by the fabric specimen using the following equation:

$$FA = (W-D)/D*100$$

15 where:

FA = fluid absorbed, %

W = wet specimen weight, g

D = initial specimen weight, g

- Step 6: Compare the fluid absorbed by the fabric specimen with the absorption capacity  
20 of the fabric specimen. The process is non-immersive if the fluid absorbed by the fabric specimen is less than about 0.8 of the absorption capacity of the fabric specimen.

The term "siloxane", as used herein, means silicone fluids which are non-polar and insoluble in water or lower alcohols. They are completely miscible in typical aliphatic and aromatic solvents, including the halogenated solvents, but are only partially miscible with the  
25 intermediate petroleum fractions such as naphthalenes. Linear siloxanes (see for example US Patents 5,443,747, and 5,977,040, both incorporated herein by reference in their entirety) and cyclic siloxanes are useful herein, including the cyclic siloxanes selected from the group consisting of octamethyl-cyclotetrasiloxane (tetramer), dodecamethyl-cyclohexasiloxane (hexamer), and preferably decamethyl-cyclopentasiloxane (pentamer, commonly referred to as  
30 "D5"). Most preferred are wash mediums wherein the siloxane comprises more than about 50% cyclic siloxane pentamer, more preferably more than about 75%, most preferably at least about 90% of the pentamer. Also preferred are wash mediums comprising siloxanes which are a mixture of cyclic siloxanes having at least about 90% (preferably at least about 95%) pentamer and less than about 10% (preferably less than about 5%) tetramer and/or hexamer.

For the present invention process, the specific method for contacting the wash medium containing the siloxane with the fabric article may be any method which results in complete wetting of the fabric articles in the wash load by the automatic washing machine, in contrast to spot wetting and/or hand wetting of the fabric articles. This includes contacting the fabric articles in an immersive bath of the wash medium or, preferably, using lower volumes of wash medium as is possible by low volume wetting means such as spraying to uniformly wet the fabric articles. Most preferred is contacting the fabric articles using a method that comprises at least one non-immersive step whereby the fabric article is wetted with the wash medium (preferably by uniform spraying), for example only to the extent of less than about 500%, more preferably less than about 200% (even more preferably less than about 150%) to about 20%, more preferably to about 50% by dry weight of the fabric article in the wash load.

One aspect of the present invention involves the contacting of the fabric articles with a wash medium comprising less than about 50% water, more preferably less than about 30%, less than about 20%, less than about 10%, less than about 5%, less than about 1%, and most preferably no purposively added water. However, in another aspect of the present invention some amount of purposively added water is a part of the wash medium with the siloxane, including for example either immiscible with the siloxane or as an emulsion comprising siloxane, water, and an emulsifying agent. Preferably the water comprises from about 0.1% to about 50%, more preferably from about 0.1% to about 30%, from about 0.1% to about 20%, from about 0.1% to about 10%, from about 0.1% to about 5%, and from about 0.1% to about 1%.

In accordance with the present invention, the fabric articles to be treated and/or cleaned may be contacted with an impinging gas at any time during the method of the present invention.

It is desirable that the fabric articles are contacted by an impinging gas at least prior to applying the cleaning fluid. The impinging gas facilitates the removal particulate soils from the fabric articles. Particulate soils can be successfully removed using gas flow. Particulate soils include any soil that is comprised of discrete particles. Nonlimiting examples of such particulate soils include clay, dust, dried mud, sand, cat fur, skin flakes or scales, dander, dandruff, hair from people or pets, grass seeds, pollen, burrs, and/or similar animal, mineral or vegetable matter which is insoluble in water.

By utilizing the impinging gas, "demand" on chemicals in the process for removing such particulate soils is reduced.

Typically, the impinging gas is flow from a gas source at a rate of from about 10 l/s to about 70 l/s and the gas contacts the fabric articles at a velocity of from about 1 m/s to about 155 m/s. It is desirable to mechanically agitate the fabric articles while the gas impinges on the fabric



articles. Further, it is desirable to remove the gas, and particulate soils in the gas from the fabric articles at a rate sufficient to prevent the removed particulate soils from re-depositing upon the fabric articles.

5 In one embodiment of the present invention the gas is selected from the group consisting of air, nitrogen, ozone, oxygen, argon, helium, neon, xenon, and mixtures thereof, more preferably air, nitrogen, ozone, oxygen, argon, helium, and mixtures thereof, even more preferably still air, ozone, nitrogen, and mixtures thereof.

10 In another embodiment of the present invention the gas used in the method can be varied over time. For example air could be used at the start of the process, a mixture of air and ozone used in the middle stages of the process and air or nitrogen could be used at the end.

The gas used may be of any suitable temperature or humidity. Heat could be supplied to the gas electrically or by passing the gas over a gas flame, such as, is done in a conventional gas dryer. However, room temperature and humidity gas are preferred.

15 In one embodiment of the present invention two or more gases could be mixed in a mixing chamber before being used in the process. In another aspect of this embodiment of the present invention the gases could be delivered concurrently through different entry points and mix in-situ in the walled vessel. In another aspect of this embodiment of the present invention the gases supplied could exist as mixture and would not require any mixing chamber to achieve the required mixture of gas for the process.

20 In one embodiment of the present invention the gas could be available from storage, such as from pressurized containers. Alternatively, the gas used in the process could be obtained from the location where the process and device occur. For example, a pump, blower, or the like, may be used to supply air from the surrounding atmosphere for the process of the invention. A combination of gas available from storage and from the atmosphere is also envisioned.

25 In another embodiment of the present invention the gas can be obtained from a compressor. The compressor may be any compressor suitable for providing gas or gases, provided that they supply the gas to the apparatus within the required velocity and flow rate ranges. The compressors are linked to the gas inlet(s) by an appropriate fixture, such as a hose, pipe, tap, fixture or combinations thereof, to provide the inlet(s) with the gas or gases within the  
30 required velocity and flow rate ranges. Some typical compressors, which are suitable for providing gas or gases, include rotary screw compressors or two-stage electrical compressor. Another suitable type of compressor is the so-called "acoustical compressor", such as those described in U.S. Patent Nos. 5,020,977, 5,051,066, 5,167,124, 5,319,938, 5,515,684, 5,231,337, and 5,357,757, all of which are incorporated herein by reference. Typically, an acoustical

compressor operates in the following fashion: A gas is drawn into a pulse chamber, such as air from the atmosphere, compressed, and then discharged as a high-pressure gas. The gas is compressed by the compressor sweeping a localized region of electromagnetic, for example microwaves, laser, infrared, radio etc, or ultrasonic energy through the gas in the pulse chamber at the speed of sound. This sweeping of the pulse chamber creates and maintain a high-pressure acoustic pulse in the gas. These acoustical compressors have many advantages over conventional compressors. For example, they have no moving parts besides the valves, operate without oil, and are much smaller than comparable conventional compressors.

In one embodiment of the present invention the gas is provided from a gas source at a rate of from about 10 l/s to about 70 l/s, more preferably, about 20 l/s to about 42 l/s, even more preferably about 25 l/s to about 30 l/s. The gas flow rate is measure by a flow meter place in the internal space of the vessel close to where the gas enters the vessel containing the clothes.

In one embodiment of the present invention the gas contacts the fabric articles at a velocity of from about 1 m/s to about 155 m/s, more preferably, about 50 m/s to about 105 m/s, even more preferably about 75 m/s to about 105 m/s. The gas velocity is measure by a flow meter place in the internal space of the vessel close to where the gas enters the vessel containing the clothes.

The velocity at which the gas contacts the fabric articles and the flow rate of the gas are critical parameters. For example insufficient velocity, means that the particulates are not removed from the fabric articles. Too great a velocity and the fabric articles are disrupted such that the fabric articles cannot be agitated and the particulate soils cannot be removed. Similarly, insufficient flow rate of the gas means that any particulate soils removed remain and can be re-deposited on the fabric article after cleaning.

Obviously the present invention process cannot use current conventional automatic washing machines as developed for aqueous wash processes. While automatic washing machines useful for the present process may be connected to a water source, such connection for purposes of carrying out the current process is solely for the supply of the optional purposively added water. A supply of the siloxane is necessary, preferably stored in a container for use in the current process and into which the siloxane is returned (following a suitable cleaning process) after contact with the fabric articles in the automatic home laundry process.

While an apparatus having the various components as defined for the immersive commercial dry cleaning process as described in US Patent 6,059,845, issued May 9, 2000, and US Patent 6,063,135, issued May 16, 2000 (both incorporated herein by reference in their entirety), if modified for residential size and consumer maintenance, could be used to practice the

present invention process, an immersive process for the present invention is not preferred. Reasons include the constraints (versus the commercial dry cleaner size and operation taught in these patents) associated with supplying, storing and cleaning larger volumes of siloxane in the home.

5 For these reasons lower volume processes such as those utilizing a uniform spray process which completely wets the fabric articles with the lower volumes of wash medium as described herein before are highly preferred. For example modifications of conventional low water wash appliances to deliver low levels of siloxane-containing wash medium rather than a water wash medium should be considered; such conventional water wash appliances are described for  
10 example in US Patents: 4,489,574; 4,489,455; 5,191,669; 5,191,668; 5,233,718; and 5,671,494, all incorporated herein by reference in their entirety. A most preferred automatic washing machine useful for this low volume process is described in detail in the co-filed, copending patent application, P&G Case 8119P, incorporated herein by reference in its entirety. Further preferred are automatic washing machines which guarantee homogeneous coverage of the fabric articles  
15 with the siloxane-containing wash medium by intermittent spin and spray followed by random tumbling until all the wash medium has been sprayed. Also preferred are such machines which reuse the siloxane-containing wash medium via an immediate re-use/recycling action, for example by passing the wash medium over a particle removal filter after extraction from the fabric articles and then immediately spraying it back onto the fabric articles.

20 Further preferred automatic washing machines for practicing the present invention processes are designed to also dry the fabric articles in the same apparatus. This not only allows the consumer the convenience of not having to handle the wet fabric articles but also permits recovery of all the siloxane for reuse or cleaning.

It is also envisioned that adjuncts for cleaning and/or treating the fabric articles according  
25 to the desires of the consumer may be added to the process. The automatic washing machine therefore preferably includes recepticals for receiving and/or dispensing such adjuncts into the automatic laundry process at the desired time, either with the wash medium or separate from it. Cartridges containing such adjuncts (either through refilling or purchased with the adjunct) which releaseably attach to the machine are also optional executions. A particularly preferred adjunct is  
30 any material which functions as an antistatic agent when combined with the siloxane-containing wash medium in the present automatic home laundry process.

An additional preferred feature of the automatic washing machine is the ability to clean and reuse the siloxane for more than one automatic laundry process. A preferred means for cleaning the siloxane for multiple uses is a replaceable filter. Such filter should preferably

- include filter materials capable of removing and collecting at least the body soils removed from the fabric articles during the automatic home laundry process. Activated charcoal, silicas, molecular sieves, and/or hydrophobically modified papers are just some optional components of such filters. The attachment to the automatic washing machine is preferably by means such that
- 5 the consumer can readily replace it at regular intervals.

What is claimed is:

1. An automatic home laundry process, said process characterized by the step of contacting fabric articles, preferably selected from the group consisting of machine washable fabric articles, dry clean only fabric articles, and combinations thereof, in an automatic washing machine in the home with a wash medium characterized by siloxane, preferably a cyclic siloxane.
2. The automatic home laundry process according to Claim 1 wherein said contacting comprises cleaning.
3. The automatic home laundry process according to Claim 1 wherein the fabric articles are contacted with the wash medium characterized by siloxane by uniformly wetting the fabric articles in the automatic washing machine.
4. The automatic home laundry process according to any of the preceding claims wherein the wash medium is characterized by no purposively added water.
5. The automatic home laundry process according to any of the preceding claims wherein the wash medium is characterized by from 0.1% to 50% purposively added water.
6. The automatic home laundry process according to any of the preceding claims wherein the cyclic siloxane is characterized by more than 50% cyclic siloxane pentamer.
7. The automatic home laundry process according to any of the preceding claims, wherein said automatic washing machine is a home automatic washing machine.
8. The automatic home laundry process according to any of the preceding claims wherein the siloxane is characterized by at least 90% by weight of the siloxane of cyclic siloxane pentamer.

# INTERNATIONAL SEARCH REPORT

Internu Application No  
PCT/US 01/18194

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 D06L1/02 C11D3/16 C11D7/50

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C11D D06L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 422 787 A (DOW CORNING) 17 April 1991 (1991-04-17) abstract page 4, line 13 - line 18; example IV	1-3,6,7
X A	GB 2 230 022 A (BP CHEM INT LTD) 10 October 1990 (1990-10-10) abstract	1-3,7 5
X A	EP 0 716 870 A (HUELS SILICONE GMBH) 19 June 1996 (1996-06-19) page 5, line 26 - line 33	1-3,7 5
A	DE 37 39 711 A (KREUSSLER CHEM FAB) 8 June 1989 (1989-06-08) example 2	1-6,8
	---	
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*Z\* document member of the same patent family

Date of the actual completion of the international search

16 October 2001

Date of mailing of the international search report

24/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Saunders, T

## INTERNATIONAL SEARCH REPORT

Intern: Application No  
PCT/US 01/18194

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 942 007 A (BERNDT DIETER R ET AL) 24 August 1999 (1999-08-24) cited in the application claims 1,3-6	1-4,6,8
A	EP 0 182 583 A (DOW CORNING) 28 May 1986 (1986-05-28) abstract	1,2,6,8

## INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat Application No

PCT/US 01/18194

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0422787	A	17-04-1991	US 5057240 A	15-10-1991
			CA 2026646 A1	11-04-1991
			DE 69026330 D1	09-05-1996
			DE 69026330 T2	02-10-1996
			EP 0422787 A2	17-04-1991
			ES 2087894 T3	01-08-1996
			JP 2749713 B2	13-05-1998
			JP 3134097 A	07-06-1991
			US 5091105 A	25-02-1992
GB 2230022	A	10-10-1990	NONE	
EP 0716870	A	19-06-1996	DE 4444175 A1	13-06-1996
			EP 0716870 A1	19-06-1996
DE 3739711	A	08-06-1989	DE 3739711 A1	08-06-1989
US 5942007	A	24-08-1999	US 5865852 A	02-02-1999
			AU 4993599 A	07-02-2000
			AU 5101799 A	07-02-2000
			BR 9912088 A	10-04-2001
			BR 9912811 A	02-05-2001
			CN 1309733 T	22-08-2001
			CN 1309734 T	22-08-2001
			EP 1084289 A1	21-03-2001
			EP 1092056 A1	18-04-2001
			NO 20010231 A	14-03-2001
			NO 20010232 A	14-03-2001
			WO 0004221 A1	27-01-2000
			WO 0004222 A1	27-01-2000
			US 6063135 A	16-05-2000
			US 6042617 A	28-03-2000
			US 6056789 A	02-05-2000
			US 6042618 A	28-03-2000
			US 6086635 A	11-07-2000
			US 6059845 A	09-05-2000
EP 0182583	A	28-05-1986	AU 585906 B2	29-06-1989
			AU 4981785 A	22-05-1986
			CA 1239326 A1	19-07-1988
			DE 3583377 D1	08-08-1991
			EP 0182583 A2	28-05-1986
			JP 1502875 C	28-06-1989
			JP 61119765 A	06-06-1986
			JP 63050463 B	07-10-1988
			US 4685930 A	11-08-1987